

Optional Features	Code
316 stainless steel top housing	YT
Stainless steel clamp rings and flanged ring – includes 300 stainless steel clamping bolts (1500 psi max)	SE
300 series stainless steel clamping bolts (maximum pressure is 1500 psi)	SB
Pipe plugs for flushing connections – pipe plugs are available in the same materials as bottom housings per Table C – see pages 64-66	PU
5000 psi pressure rating – (Type 100/200 only) threaded inlet only, no flushing connection (metal diaphragm only) 7500 psi pressure rating (T-400)	HP
Welded instrument to diaphragm seal	DU
Dual flushing connections (1/2 NPT) (Limited to 2" thru 3" flanged seals)	DB
Ring joint	RJ
Flat face	FF
No Teflon gasket. Special matching on bottom housing (2)	NX
Clean for gaseous oxygen or strong oxidizing agent applications (3)	6B
For accessories – see pages 243-250	—

Multiple Instruments Attached to Diaphragm Seals

Code	Description
XH3	02L Gauge Connection, 1/4 NPT Transducer, 02T Seal Connection
XH5	04L Gauge Connection, 1/2 NPT Switch, 02T Seal Connection
XH6	04L Gauge Connection, (2) 1/2 NPT Switches, 02T Seal Connection
XH7	02L Gauge Connection, 1/4 NPT Female Switch, 02T Seal Connection
XH8	02L Gauge Connection, (2) 1/4 NPT Instruments, 02T Seal Connection
XH9	02L Gauge Connection, 1/2 NPT Female Switch, 04T Seal Connection
XL3	02L Gauge Connection, 1/4 NPT Female Switch, 02T Seal Connection, 1/4 NPT Snubber (separate line item)