

Model K1 Pressure Transmitter



LOOK FOR THIS AGENCY
MARK ON OUR PRODUCTS



APPLICATIONS

Hydraulic, refrigeration, machine tool, test/measurement, pump control, HVAC, medical, construction equipment and all general purpose industrial process applications

FEATURES:

- 0.5% and 1.0% accuracy
- Vac.-20,000 psi pressure range
- FM approved (optional)
- Superior long-term stability and repeatability
- Stainless steel NEMA 4X enclosure
- Current/voltage output
- Wide range of electrical connections available
- Optional panel meter digital display – see Ashcroft model 2269

The Ashcroft® K1 is a proven and versatile pressure transducer/transmitter incorporating polysilicon thin film technology. Modern low-pressure chemical vapor deposition methods provide simple, stable molecular bonds between the metal diaphragm and a polysilicon strain gage bridge. There are no epoxies or bonding agents to contribute to signal instability or drift. The integral metal diaphragm and polysilicon bridge are virtually unaffected by shock, vibration or mounting.

These transmitters are offered in many standard pressure ranges with either current or voltage output signals. Transmitter performance is directly traceable to the National Institute of Standards and Technology. A calibration test certificate is available with each transmitter.

PERFORMANCE SPECIFICATIONS

Accuracy Class (Span): ±0.5% ±1.0%
Includes non-linearity (Terminal Point Method), hysteresis, non-repeatability, zero offset and span setting errors
Best Fit Straight Line (BFSL) ±0.25% ±0.4%
Non-linearity
Interchangeability ±0.5% ±1.0%
Durability: 10⁸ cycles 20/80% span with negligible performance change
Stability: ±0.5% Span/yr

ENVIRONMENTAL SPECIFICATIONS

Temperature Limits:

Storage: -54 to 121°C (-65 to +250°F)
Operating: -28 to 82°C (-20 to +180°F)
Comp. Range: -28 to 71°C (-20 to +160°F)

Thermal Coefficients: (68°F (20°C) ref.) % Span/°F:

Accuracy Class: 0.5% 1%
ZERO ±0.028% ±0.04%
SPAN ±0.028% ±0.04%

Optional (0.5% Accuracy Class only):

ZERO ±0.014% N/A
SPAN ±0.014% N/A

Multiply thermal zero coefficients by 1.5 on 0/30 psi, vac/15 range and by 3 on 0/15 and vac/0 ranges

Humidity: No performance effect at 95% relative humidity-noncondensing

FUNCTIONAL SPECIFICATIONS

Standard Ranges (psi) gauge, compound:

0/15*	0/300	0/5000	vac./60*
0/30*	0/500	0/7500*	vac./45*
0/60*	0/750	0/10,000*	vac./30*
0/100	0/1000	0/15,000*	vac./15*
0/150	0/2000	0/20,000*	vac./0*
0/200	0/3000		

*1% accuracy ranges only.

Consult factory for nonstandard ranges\.

Overpressure Limits (F.S.):

	15- 2000	3000- 5000	7500- 20,000
Proof	200%	150%	120%
Burst	800%	300%	150%

Vibration Sweep: Less than ±0.1%F.S. effect for 0-2000 Hz at 20 g's in any axis

Shock: Less than ±0.05% F.S. effect for 100 g's, 20ms shock in any axis

Response Time: Less than 5 ms

Position Effect: Less than 0.01% F.S.

ELECTRICAL SPECIFICATIONS

Output Signal (consult factory for options):

4-20mA (2 wire)
1-5 Vdc (3 wire)
1-6 Vdc (3 wire)
1-11 Vdc (3 wire) (minimum excitation 15 Vdc)

Power Requirements: 10-36 Vdc unregulated, <3mA for voltage output

