

Optional Features 1010, 1017 & 1220 Refrigeration Gauges

Case and Ring Options	Code	Comments
Flush Mounting Ring (black)	50	Available on 4½" 6" Type 1010 back connection.
Flush Mounting Ring (black)	20	Available on 12" Type 1010 back connection.
Flush Mounting Ring (polished SS)	53	Available on 4½" 6" Type 1010 back connection.
Stainless Steel Polished Ring	63	Available on 4½" 6", and 8½" Type 1010.
Chrome Plated Ring	13	Available on Type 1010, 1017.
Flush Mounting Ring (black)	54	Available on 1220 back connection.
Flush Mounting Ring (chrome plated steel)	55	Available on 1220 back connection.
Bourdon Tube and System Assembly Options		
Overload Stop	OS	Used to protect the gauge against pressures beyond the gauge range.
Underload Stop	VS	Used to protect low pressure gauges against vacuum.
Tons-on-Ram Gauge	TR	Includes throttle screw, slotted link and special dial. Consult customer service for dial availability.
Movement Options		
Stainless Steel Movement	SM	Option includes all stainless steel components.
Sudden Increase Link	RJ	Designed to protect the gauge from sudden pressure surge on increase.
Sudden Decrease Link	S4	Designed to protect the gauge from sudden pressure surge on decrease.
PLUS! Performance	LL	Liquid-filled performance in a dry guage.
Special Connections		
Ashcroft Types 1010, 1017 and 1220 are available but not limited to SAE, DIN, BSP, JIS and UNF connections. Consult customer service regarding your requirements.		
Pointer Options		
Friction Adjustable	AP	Available on all sizes and types (excludes 12" Type 1010).
Micrometer Adjustable	MP	Available on all sizes and types (excludes 12" Type 1010).
Stationary Red Set-Hand (single)	SH	Available on all sizes and types.
Maximum Pointer	EP	Externally reset by a knob on outside of an acrylic window.
Minimum Pointer	EQ	Externally reset by a knob on outside of an acrylic window.
Window Options		
Acrylic Window	PD	Available on all sizes and types (excludes 12" Type 1010).
Laminated Safety Glass	SG	Available on all sizes and types (excludes 12" Type 1010).
Marking and Tagging Options		
Dial Marking	DA	Service marking printed on dial.
Paper Tagging of Carton and Gauge	NN	Tag is bonded to gauge case.
Stainless Steel Tag, Wired	NH	Stainless steel tag is wired to gauge case.
Stainless Steel Tag, Bonded	MN	Stainless steel tag is bonded to gauge case.
Calibration Options		
Absolute Pressure	AB	Involves offset of pointer. Consult customer service for details.
Special Cleaning Options		
Cleaning for Gaseous Oxygen Service ⁽¹⁾	6B	In accordance with ASME B40.1, Level IV.
Dial Options		
White Dial	WN	White dial with black numerals.
Black Dial	BD	Black dial with white numerals. Furnished with a white pointer. Consult Customer Service for dial availability.
Refrigeration/Ammonia Dials	R1-R9	

(1) Not available on A, B, or R tubes.