NSF International

789 N. Dixboro Road, Ann Arbor, MI 48105 USA

RECOGNIZES

Ashcroft Inc.

Stratford, CT

AS COMPLYING WITH NSF/ANSI/CAN 61 AND ALL APPLICABLE REQUIREMENTS. PRODUCTS APPEARING IN THE NSF OFFICIAL LISTING ARE AUTHORIZED TO BEAR THE NSF MARK.







This certificate is the property of NSF International and must be returned upon request. This certificate remains valid as long as this client has products in NSF's Official Listings for the referenced standards. For the most current and complete Listing information, please access NSF's website (www.nsf.org).

Sheresa Bellish

July 17, 2024 Certificate# C0778906 - 01

Theresa Bellish

Senior Director Municipal Water Systems and NA Region

NSF International

789 N. Dixboro Road, Ann Arbor, MI 48105 USA

RECOGNIZES

Ashcroft Inc.

Facility: Stratford, CT

AS COMPLYING WITH NSF/ANSI/CAN 61 AND ALL APPLICABLE REQUIREMENTS. PRODUCTS APPEARING IN THE NSF OFFICIAL LISTING ARE AUTHORIZED TO BEAR THE NSF MARK.







This certificate is the property of NSF International and must be returned upon request. This certificate remains valid as long as this client has products in NSF's Official Listings for the referenced standards. For the most current and complete Listing information, please access NSF's website (www.nsf.org).

Theresa Bellist

July 17, 2024 Certificate# C0778907 - 01

Theresa Bellish

Senior Director Municipal Water Systems and NA Region



OFFICIAL LISTING

NSF Certifies that the products appearing on this Listing conform to the requirements of NSF/ANSI/CAN 61 - Drinking Water System Components - Health Effects

This is the Official Listing recorded on August 30, 2024.

Ashcroft Inc.
250 East Main Street
Stratford, CT 06614-5145
203-378-8284

Facility: Stratford, CT

Mechanical Devices

Trade Name	Size	Water Contact Temp	Water Contact Material
Pressure Gauges [G]			
1008-S Pressure Gauge[1]	1/8 - 1/2 in.	C. HOT	MLTPL
1009-SW Duralife® Pressure Gauge[1]	1/8 - 1/2 in.	C. HOT	MLTPL
1279-S Duragauge® Pressure Gauge[1]	1/8 - 1/2 in.	C. HOT	MLTPL
Miscellaneous Process Devices/Components [G]			
Type 200 Threaded Diaphragm Seal[2]	1/8 - 2 in.	C. HOT	MLTPL
Type 201 Threaded Diaphragm Seal[2]	1/8 - 2 in.	C. HOT	MLTPL
Type 80 Wafer Isolation Ring[3]	2 - 20 in.	C. HOT	MLTPL
Type 81 Bolt-thru Isolation Ring[3]	1 - 10 in.	C. HOT	MLTPL
Type 82 Threaded Isolation Ring[3]	1/2 - 2 in.	C. HOT	MLTPL
Switches/Sensors [G]			
A Series Miniature Pressure Switch[4]	1/8 - 2 in.	C. HOT	MLTPL
B Series Pressure Switch[5]	1/4 - 1/2 in.	C. HOT	MLTPL
G2 Series Pressure Transducer	1/8 - 3/8 in.	C. HOT	MLTPL
G3 Series Pressure Transducer	1/8 - 3/8 in.	C. HOT	SS
G Series Pressure Switch[5]	1/4 - 1/2 in.	C. HOT	MLTPL

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF.



L Series Pressure Switch[5]	1/4 - 1/2 in.	C. HOT	MLTPL
P Series Pressure Switch[5]	1/4 - 1/2 in.	C. HOT	MLTPL
T2 Series Pressure Transducer	1/8 - 3/8 in.	C. HOT	MLTPL

- [1] Certified for stainless steel tube and process connection only.
- [2] Certified for a stainless steel diaphragm and bottom housing only. Any components can be used above the diaphragm seal as they do not have water contact.
- [3] Certified for SS316L end plate and EPDM liner. Any components can be used above the isolation ring as they do not have water contact.
- [4] Models that have an o-ring are approved for NBR o-rings only.
- [5] Certified for PTFE or stainless steel diaphragm and stainless steel process connection only.
- [G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF.