












Keep your critical equipment and processes running with reliable temperature measurements.

RTDs & Thermocouples

S01 RTD & Thermocouple Inserts	S10 RTD & Thermocouple Probes with Metric Connections	S50 RTD & Thermocouple Probes with NPT Connections	S70 Probes with Tube Skin Connections	S80 & S81 Probes with Extension Cable	S40 & S41 Thermocouple Probes for High Temperature Applications	S96 Multipoint Temperature Assemblies
						
Thermocouple Types: J, K, T, E, N	Thermocouple Types: J, K, T, E, N	Thermocouple Types: J, K, T, E, N	Thermocouple Types: J, K, N	S80 Thermocouple Types: J, K, T, E, N	S40 Common Metal Sensor up to 1200 °C (2192 °F)	S96 Multipoint Straight or Flexible Assemblies
RTDs: 100 or 1000 Ohm, 2, 3, or 4 wire	RTDs: 100 or 1000 Ohm, 2, 3, or 4 wire	RTDs: 100 or 1000 Ohm, 2, 3, or 4 wire	RTDs: Available on request	S81 RTDs: 100 or 1000 Ohm, 2, 3, or 4 wire	S41 Precious Metal Sensor up to 1800 °C (3272 °F)	S96 Multipoint: Lengths up to 300 m (1,000 ft)

Mechanical Temperature

Duratemp® Gas Actuated Thermometer	CI Bimetal Thermometer	EI Bimetal Thermometer	S5500 Gas Actuated Thermometer
			
Temperature Range -320 °F to 1200 °F (-200 °C up to 650 °C)	Temperature Range -80/120 °F to 200/1,000 °F (-60/50 °C to 100/550 °C)	Temperature Range -80/120 °F to 200/1,000 °F (-60/50 °C to 100/550 °C)	Temperature Range -330 °F/120 °F to 32 °F/1450 °F -200 °C/50 °C to 0 °C/800 °C

Thermowells

Threaded	Flanged	Van Stone	Socket Weld	Weld-In	Sanitary	Vortex
						
Process Connection 1", 1.5", 2", 3", & 4" Pipe Size	Process Connection ½, ¾, 1 NPT	Process Connection 1", 1.5", 2", 3", & 4" Pipe Size	Process Connection ¾" & 1" Pipe Size	Process Connection 1.5" Pipe Size	Process Connection 1", 1.5", & 2" Tri-Clamp®	Process Connection 1.5" & 2" Pipe Size
MATERIALS - Variety of metallic materials available						

Contact Us

+ 1 800-328-8258
ashcroft.com

All specifications are subject to change without notice. All sales subject to standard terms and conditions. Ashcroft®, Duratemp®, Trust the Shield® are trademarks of Ashcroft Inc. The following non-Ashcroft trademarks are the property of their respective owners: Tri-Clamp®. For more information, see [Ashcroft Brands & Trademarks](#) ©2026 Ashcroft Inc. temp_plc_RevC_07-May-2026